



SUPRA[®] 860

RESTAURANT

**Superior refrigeration
performance for large trucks.**



PERFORMANCE SPECIFICATIONS

SUPRA[®] 860

Supra 860 unit offers exceptional reliability and performance for better load protection and quality in larger trucks.

Supra 860 unit delivers increased performance and system life while reducing maintenance and service costs.

- **Superior capacity and airflow** offer maximum product protection.

- **Extended service intervals** for maximum asset utilization.

- **Heavy-duty, high-displacement compressor** runs slower for exceptional operating life.

- **Combines all the latest technological developments** to offer maximum reliability, performance, and flexibility.

Accessories and Options:

Battery (dealer-supplied)
Battery box
30-gallon fuel tank
50-gallon fuel tank
Fuel heater
Top debris protection grille
High-voltage electric standby
460v-3ph-60Hz
Supply-air control
Stealth noise reduction kit
Host system door shutdown switch
Coolant heat system (diesel operation)
Electric heat system (standby operation)



Condenser Dimensions

71.7" x 33.7" x 24.7"
(1,823 x 856 x 629 mm)

Evaporator Dimensions

48.2" x 28.8" x 13.0"
(1,225 x 732 x 330 mm)

Body Opening

49.0" x 13.8"
(1,245 x 350 mm)

Approximate Weights:

TDB-24: 1,020 lb (462 kg) without standby
TDS-24: 1,055 lb (478 kg) with standby

Cooling/Temperature Capacity:
Ambient at 100°F (38°C)
Speed: 2,300 rpm diesel/60-hertz
electric operation

Evaporator Return Air Temp.	Diesel Operation		Standby Operation	
	Btuh	Watts	Btuh	Watts
35°F (2°C)	23,000	6,740	22,000	6,450
0°F (-18°C)	15,500	4,745	15,000	4,395
-20°F (-29°C)	10,000	2,930	9,500	2,785

Standard Features Include:

CT3-44 TriVortex diesel engine
05K24 4-cylinder compressor
Automatic hot-gas heating system
Refrigerant R-404A
Three-way refrigeration valve system
Standard with electric standby (model TDS)
Heavy-duty electric standby motor:
208v/230v-3ph-60Hz
or 220v-3ph-50Hz
Remote-mount power receptacle
Microprocessor control system
CAB COMMAND™ remote control center
Critical Cargo Monitor (in cab)
Audible temperature alarm (in cab)
Red light visual warning alarm (in cab)
Automatic pretrip system
Lighted CAB COMMAND keys
Main on/off system power switch
Display indicators
Cool-Heat-Defrost
Start/Stop-Out of Range
Engine Operation-Electric Standby
Digital readout
CAB COMMAND (in cab)
Engine coolant temperature
Unit suction pressure
Battery voltage
Engine run hours
Electric standby hours

Standard Features (continued):

Maintenance interval hours
Total on-time hours
Setpoint temperature
Box return-air temperature
Automatic Start/Stop fuel saver
City Speed control
Automatic defrost control
Extended-life antifreeze
High coolant temperature protection
High-power 105-amp alternator
Low engine oil protection
High refrigerant pressure protection
Low refrigerant pressure protection
Receiver tank pressure relief
Bottom panel
Installation package
Electric fuel pump
Fuel lines
Battery cables
Installation hardware
Fuel tank pickup tubes

Specifications are subject to change without notice.

Warranty: Product warranty and limitations are outlined in Form 62-10857. This warranty applicable only in North America. Consult your Carrier Transicold representative for warranty coverage elsewhere. Form 62-11686.

North America
Carrier Transicold
700 Olympic Drive
Athens, GA 30601 USA
Tel: 706-357-7223
Fax: 706-355-5435

**Central America
and Mexico**
Ejercito Nacional 253-A Piso 5
Colonia Anahuac
11320 Mexico D.F.
Ph: (5255) 5531-5010
Fax: (5255) 5531-5010 ext.1005



©2013 Carrier Corporation. Printed in USA 0313.



**United
Technologies**

Climate | Controls | Security

Carrier Transicold Division
Truck/Trailer Products Group
P.O. Box 4805
Syracuse, NY 13221 USA

www.trucktrailer.carrier.com